

**BIOLOGICZNE OCZYSZCZALNIE ŚCIEKÓW**  
(oczyszczalnie przydomowe)

<b>Typ BOŚ</b>	<b>RLM</b> (ilość osób)	<b>Max. dzienny przepływ</b> (m <sup>3</sup> /d)	<b>Ładunek zanieczyszczeń</b> (BZT <sub>5</sub> /d)	<b>Moc</b> (230V/400V)	<b>Zużycie energii</b> (kWh/d)
Topas 5	1-5	1,0	0,30	60W	1,44
Topas 8	2-8	1,5	0,48	80W	1,92
Topas 10	3-10	2,0	0,60	100W	2,40
Topas 15	3-15	3,0	0,90	120W	2,88
Topas 20	4-20	4,0	1,20	150W	3,60
Topas 30	6-30	6,0	1,80	240W	5,76
Topas 40	8-40	7,0	2,40	300W	7,20
Topas 50	10-50	9,0	3,00	400W	9,60
Topas 75	15-75	12,0	4,50	750W	18,00
Topas 100	20-100	15,0	6,00	750W	18,00
Topas 125	25-125	18,75	7,50	1500W	36,00
Topas 150	30-150	22,5	9,00	1500W	36,00
Topas 200	35-200	30,0	12,0	2200W	52,80
Topas 250	40-250	37,5	15,0	2200W	52,80
Topas 300	45-300	45,0	18,0	2200W	52,80
Topas 400	50-400	60,0	24,0	4000W	96,00